

301-CI9201-0000

Multi-Conductor - Shield Twisted Pair Cable







DECRIPTION

22 AWG stranded (7x30) tinned copper conductor, polyethylene insulation, twisted pair, aluminum shield (125% coverage), 22 AWG stranded tinned copper drain wire, PVC jacket.

APPLICATION

Multipair Audio, Control and Instrumentation Cable for Industrial, Data, Interconnect and Analogue Audio used.

PHYSICAL CHARACTERISTICS

Conductor

AWG

Pair	AWG	Stranding	Conductor Material
1	22	7x30	TC – Tinned Copper

Insulation

Insulation Material

Insulation Material	Wall Thickness (mm)
PE – Polyethylene	0.41

Outer Shield

Outer Shield Material

Туре	Outer Shield Material	Coverage
Tape	Aluminum Mylar	125%

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC – Tinned Copper

Outer Jacket

Outer Jacket Material

Outer Jacket Material	Nom. Wall Thinkness (mm)
PVC – Polivinyl Choloride	0.64

Overall Cabling

Overall Nominal Diameter: 4.3 mm

Pair

Pair Color Code Chart

i un coloi	Jour Griant		
Number	Color		
1	Black & Clear		



Mechanical Characteristics (Overall Cable)

Operating Temperature Range	-20°C to 60°C		
Temperature Rating	60°C		
Max Pulling Tension	28 Kg		
Min. Bend Radius	57.15 mm		

Applicable Specifications and Agency Compliance (Overall Cable)

Applicable Standards

EU CE Mark (Y/N)	Yes
EU Directive 2002/95/EC (RoHS) (Y/N)	Yes
EU RoHS (Y/N)	Yes

Electrical Characteristics (Overall Cable)

Nom. Characteristic Impedance

Noni. Characteristic impedant
Impedance (Ohm)
57

Nom. Inductance

Inductance (µH/ft)
0.18

Nom. Capacitance Conductor to Conductor

Capacitance (pF/ft)	
29.8	

Nom. Capacitance Cond. to Other Conductor & Shield

 - u	paorta		00110		011101	•
(Capac	itano	ce (pF	/ft)		
		11				

Nom. Conductor DC Resistance

DCR@20°C (Ohm/1000ft)
6	8

Max. Operating Voltage

 operating remage	
Voltage	
300	

Max. Operating Current

Current/Cond.	@ 25°C
5.2A	

Part Number

301-Cl9201-0000 1 Pair 22 AWG Shielded Twisted Cable



Product Family

301-Cl9202-0000	2 Pair 22 AWG Shielded Twisted Cable
301-Cl9203-0000	3 Pair 22 AWG Shielded Twisted Cable
301-Cl9204-0000	4 Pair 22 AWG Shielded Twisted Cable

© Alantek Communications USA All Right Reserved.

Alantek® Communications USA 2006. This information provides a general description of product and shall not form part of any contract. Improvement or changes may be made to the product without advanced notification.